





SPECIAL CONNECTORS



Technical drawing					
Product description					
Connector type	Y splitter connector		Y splitter connector	Y splitter connector	Y splitter connector
Conforms to	-		-	-	-
Construction type	M12 A -Coding		M12 A -Coding	M12 A -Coding	M12 A -Coding / M8 A-coding
Part number	12T34000		12T35000	12T45000	12T308F
Description	M12 Y splitter connector with SHUNTING circuit		M12 Y splitter connector with PARALLEL circuit	M12 Y splitter connector with 3 LED, PNP circuit	M12 Y splitter connector with N,2 M8 conn. with SHUNTING circuit
Contacts type	Side A	M12 Female	M12 Female	M12 Female	M8 Female
	Side B	M12 Female	M12 Female	M12 Female	M8 Female
	INPUT side	M12 Male	M12 Male	M12 Male	M12 Male
Number of contacts	Side A	4poles	5poles	4poles	3poles
	Side B	4poles	5poles	4poles	3poles
	INPUT side	5poles	5poles	5poles	4poles
Housing colour	Black		Black	Transparent	Black
Technical data					
Housing material	Polypropylene		Polypropylene	Polypropylene	Polypropylene
Contacts material	Brass + Gold flash		Brass + Gold flash	Brass + Gold flash	Brass + Gold flash
Coupling nut type	Knurl round		Knurl round	Knurl round	Knurl round
Coupling nut material	Brass + Nickel plated		Brass + Nickel plated	Brass + Nickel plated	Brass + Nickel plated
Internal core material	PA66-V2		PA66-V2	PA66-V2	PA66-V2
M12 coupling nut torque	0.4 N*m		0.4 N*m	0.4 N*m	M12: 0.4 N*m / M8: 0.2N*m
Circuit type	Shunting		Parallel	3 LED PNP	Shunting
Rated voltage	60V AC/DC		60V AC/DC	24V AC/DC	60V AC/DC
Rated current	4A		4A	4A	3A
O-ring material	NBR		NBR	NBR	NBR
Fixing type	no. 1 fixing hole		no. 1 fixing hole	no. 1 fixing hole	no. 1 fixing hole
Fixing hole diameter	ø 3.20mm		ø 3.20mm	ø 3.20mm	ø 3.20mm
Packaging					
Qty/Bag	1 pc / bag		1 pc / bag	1 pc / bag	1 pc / bag
Other accessories options					
See accessories section					
Notes:					